

## 293 liter tank i Syrafast 316

SOFAST					
33291 BLANQUEFORT Z.I.					
Construit pour : : riob D					
N° de type : CP 250		N° de fabrication : 2074			
Catégorie de risque : II		Année de construction : 2021			
CUVE		D.E		CUVE	
D.E		D.E		D.E	
P.S. : 3 Bar		2 Bar		Volume : 293 L	
11 L		T.S. mini : 5 °C		5 °C	
T.S. maxi : 150 °C		150 °C		Groupe : 2	
2		Date éprouve: 15/12/2021		2	
P.T. : 5,5 Bar		3,5 Bar		Vide admissible : -1 Bar	
-1 Bar		Masse à vide : 415 Kg		Masse maxi. en éprouve: 708 Kg	
CODE		INSPECTION		CE	
CODAP 2015 DIV 2		O.N. : 0060			
Cat. : B2					
Coef. soudure : 0,85					

**328,000,00 kr /st exkl moms**

**Additional information:** pharmacy; mobile frame V2A with brake; hand hole with sight glass diameter: approx. 250mm; pneumatic actuator at the outlet; the container hangs on 3x weighing cells on the frame

**Volumetric volume (L):** 293 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 3 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 150 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** single jacketed with heat-exchanger

**Heat exchanger:** yes

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 11 L

**Max Overpressure:** 2 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 150 °C

**Type HE on the cylinder:** heating/cooling jacket

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** in the bottom

**Outlet of tank:** clamp

**Agitator:** yes

**Number of revolutions:** 2.825

**Power:** 0,55

**Internal diameter tank:** 636 mm

**Cylinder height:** 750 mm

**Total height of tank:** 1.880 mm

**Total outer width:** 850 mm

**Total outer length:** 1.500 mm

**SKU:** 437435

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: pharmacy; mobile frame V2A with brake; hand hole with sight glass diameter: approx. 250mm; pneumatic actuator at the outlet; the container hangs on 3x weighing cells on the frame; we can't give any

Övrig information2: guarantees about the agitator

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 293

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316



## Dimensioner av tank

Cylinderhöjd: 750 mm

Invändig diameter: 636 mm

Total höjd: 1.880 mm

## Omrörare

Kraft (kW): 0,55

Varvtal: 2.825

## Mer

Isolerad: Nej