

29370 liter tank i Syrafast 316



912,000,00 kr /st exkl moms

Article type: second-hand pressure tank

Additional information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Volumetric volume (L): 29.370 L

Ra inner weld: 0,80

Pressure in tank: pressure

Design pressure (Bar): 5,20 Bar

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): -1 Bar



Max. temperature (°C): 150 °C

Material wet parts: SS AISI 316L (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: dished

Total discharge: yes

Fixation points: 4 supports for platform

Type of HE on the cylinder: dimple-jacket

Position HE: the lower part of the cylinder

Height HE: 3.200 mm

Water pressure HE: 6 Bar

Steam pressure HE: 4 Bar

Hydraulic test pressure: 9,70 Bar

Working temperature HE cylinder: 150 °C

Type of HE on the bottom: dimple-jacket

Water pressure HE: 6 Bar

Working temperature HE bottom: 150 °C

Suitable for food industry: yes

Documents included: no

Technical drawing included: yes

Registration plate on the tank: yes

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 600 mm

Agitator: yes

Agitator type: tripod

Position engine: at the top

Power: 23,50

Voltage: three-phase

Internal diameter tank: 2.686 mm

Outer diameter tank: 2.936 mm

Cylinder height: 4.500 mm

Empty weight tank: 2.800

SKU: 184033

Mer information
