295 liter tank i Syrafast 316



PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

51 000 SEK /st exkl moms

Additional information: incl. pump and UV reactor
Volumetric volume (L): 295 L
Pressure in tank: pressure
Max. pressure (Bar): 0,50 Bar
Min. pressure (Bar): 0,50 Bar

Max. temperature (°C): 100 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 9 L
Max Overpressure: 3 Bar

Max. working temperature: 50 °C
Type HE on the cylinder: heating/cooling jacket
Heat exchanger: RVS 304
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Outlet of tank: available
Internal diameter tank: 500 mm
Cylinder height: 1.340 mm

Total height of tank: 2.100 mm

SKU: 392876

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 100 °C
Mobil tank: Nej
Övrig information: Pharmazie; inkl. Pumpe und UV-Reaktor; we can’t give any guarantees about the heating/cooling jacket
Omrörare: Nej
Övertryck: 0,50 Bar
Total urtappning: Ja
Undertryck (vakuum): 0,50 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 295

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.340 mm
Invändig diameter: 500 mm
Total höjd: 2.100 mm

Mer

Värmeväxlare: RVS 304
Isolerad: Ja