

2950 liter tank i Syrafast 316



129,000,00 kr /st exkl moms

Additional information: Pharmacy; 4 stainless steel 304 brackets; total height indicated is estimated

Volumetric volume (L): 2.950 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 2,50 Bar

Min. pressure (Bar): 0,90 Bar

Max. temperature (°C): 138 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Total discharge: yes

Volume: 148 L

Max Overpressure: 5 Bar

Max onderdruk: 0,90 Bar

Max. working temperature: 151 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: available

Agitator: yes

Number of revolutions: 1.475

Power: 15

Top: 5,70 mm

Cylinder: 10 mm

Bottom: 7 mm

Internal diameter tank: 1.400 mm

Outer diameter tank: 1.600 mm

Cylinder height: 1.500 mm

Total height of tank: 3.500 mm

SKU: 489357

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 138 °C

Mobil tank: Nej

Övrig information: Pharmacy; 4 stainless steel 304 brackets; total height indicated is estimated; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 2,50 Bar

Total urtappning: Ja

Undertryck (vakuum): 0,90 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 2950

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.500 mm
Invändig diameter: 1.400 mm
Total höjd: 3.500 mm
Ytterdiameter: 1.600 mm

Omrörare

Kraft (kW): 15
Varvtal: 1.475

Tjocklek på tank

Botten: 7 mm
Cylinder: 10 mm
Topp: 5,70 mm

Mer

Isolerad: Ja