2950 liter tank i Syrafast 316



130 000 SEK /st exkl moms

Additional information: 4 stainless steel 304 brackets; total height indicated is estimated
Volumetric volume (L): 2.950 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 2,50 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 0,90 Bar

Max. temperature (°C): 138 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: insulated
Heat exchanger: no

Insulation: yes
Mobile tank: no
Total discharge: yes
Volume: 148 L
Max Overpressure: 5 Bar

Max. working temperature: 151 °C
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: available
Agitator: yes

Number of revolutions: 1.475
Power: 15
Top: 5,70 mm
Cylinder: 10 mm
Bottom: 7 mm

Internal diameter tank: 1.400 mm
Outer diameter tank: 1.600 mm
Cylinder height: 1.500 mm
Total height of tank: 3.500 mm

SKU: 489357

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 138 °C
Mobil tank: Nej
Övrig information: Pharmacy; 4 stainless steel 304 brackets; total height indicated is estimated; we can’t give any guarantees about the heating/cooling jacket; we can’t give any guarantees about the agitator
Omrörare: Ja
Övertryck: 2,50 Bar
Total urtappning: Ja
Undertryck (vakuum): 0,90 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 2950

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 1.500 mm
Invändig diameter: 1.400 mm
Total höjd: 3.500 mm
Ytterdiameter: 1.600 mm

Omrörare
Kraft (kW): 15
Varvtal: 1.475

Tjocklek på tank
Botten: 7 mm
Cylinder: 10 mm
Topp: 5,70 mm

Mer
Isolerad: Ja