300 liter tank i Syrafast 316



173 000 SEK /st exkl moms

item available on order

Article type: brand new mixing tank - type VC-HICA
Additional information: example picture; delivered with food certificate; *article price without agitator; choice of 2 different types of agitators; see options; (The article can also be purchased without options)*; Ra=<0.8µm
Volumetric volume (L): 300 L
Max. density P (kg/m³): 1.200
Ra inner weld: 0,80

Finish stainless steel: 2b
Pressure in tank: ATM - atmosferic

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. temperature (°C): 100 °C
Min. temperature (°C): -10 °C
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes
Insulation: no
Mobile tank: yes

Top type: half hinging lid °
Shape of tank: cylindrical
Bottom type: conical 10 °
Total discharge: yes
Fixation points: 4 casters

Type of HE on the cylinder: dimple-jacket
Position HE: the complet cilinder
Water pressure HE: 3 Bar
Hydraulic test pressure: 4 Bar
Working temperature HE cylinder: 130 °C

Heat exchanger: RVS 304
Insulation material: Rockwool
Outer jacket (ornamental wall): RVS 304
Valve: RVS 316L
Fixation point(s): RVS 304

Suitable for food industry: yes
Documents included: yes, optional
Technical drawing included: yes
Registration plate on the tank: yes
Flange for agitator: yes

CIP spray ball: no, optional
Tank outlet: inside Ø 40 mm
Outlet type: DIN11851
Total outlet valve: no, optional
Agitator: no, optional

Top: 3 mm
Cylinder: 3 mm
Bottom: 3 mm
Cylinder: 2
Insulation body: yes

finish of the outer jacket: welded
Insulation thickness: 40
Outer diameter tank: 763 mm
Total height of tank: 1.760 mm
Empty weight tank: 136

SKU: 377156

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Nytillverkad
Arbetstryck i tank: ATM – atmospheric
Finish rostfritt stål: 2b
Konfiguration: isolert med varmeveksler
Max. arbetstemperatur: 100 °C
Maximal densitet för produkten: 1200
Min. arbetstemperatur: -10 °C
Mobil tank: Ja
Övrig information: example picture; delivered with food certificate; article price without agitator; choice of 2 different types of agitators; see options; (The article can also be purchased without options);
Övrig information2: Ra=<0.8µm
Omrörare: Nej
Ra innersvets: 0,80
Tankens form: cylindrical
Total urtappning: Yes
Typ av botten: conical 10 °
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 300

Utrustning

Fläns för omrörare: Ja
Märkskylt: Ja
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 40 mm
Teknisk ritning finns: Ja
Utloppstyp: DIN11851

Översikt material

Material: Syrafast 316
Fixeringspunkt(er): RVS 304
Isoleringsmaterial: Rockwool
Ytterbeklädnad: RVS 304

Dimensioner av tank

Total höjd: 1.760 mm
Ytterdiameter: 763 mm

Värmeväxlare

Arbetstemperatur värmeväxlare cylinder: 130 °C
Hydrauliskt provtryck botten: 4 Bar
Hydrauliskt provtryck: 4 Bar
Position värmeväxlare: the complet cilinder
Typ av värmeväxlare på cylinder: dimple-jacket
Vattentryck värmeväxlare: 3 Bar

Tjocklek på tank

Botten: 3 mm
Cylinder: 3 mm
Topp: 3 mm

Tjocklek på ytterbeklädnad och isolering

Finish utvändig mantel: welded
Isolering mantel: Ja
Isoleringsmaterial: Rockwool

Mer

Värmeväxlare: RVS 304
Cylinder OW: 2
Isoleringstjocklek OW: 40
Isolerad: Nej
Vikt: 136