300 liter tank i Syrafast 316



PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

107 000 SEK /st exkl moms

item available on order

Article type: brand new mixing tank - type VC-SLA
Additional information: delivered with food certificate; *article price without agitator; choice of 2 different types of agitators; see options; (The article can also be purchased without options);* Ra=<0.8µm
Volumetric volume (L): 300 L
Max. density P (kg/m³): 1.200
Ra inner weld: 0,80

Finish stainless steel: 2b
Pressure in tank: ATM - atmosferic
Max. temperature (°C): 80 °C
Min. temperature (°C): -10 °C
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

Top type: half hinging lid °
Shape of tank: cylindrical
Bottom type: conical 10 °
Total discharge: yes
Fixation points: 3 non adjustable feet

Valve: RVS 316L
Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: yes, optional
Technical drawing included: yes

Registration plate on the tank: yes
Flange for agitator: yes

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

CIP spray ball: no, optional
Tank outlet: inside Ø 40 mm
Outlet type: DIN11851

Total outlet valve: no, optional
Agitator: no, optional
Agitator type: propeller agitator
Position engine: at the top
Number of revolutions: 1.410

Power: 0,37
Voltage: three-phase
Agitator type 2: propeller agitator
Position engine: at the top
Number of revolutions: 750

Power: 0,25
Voltage: three-phase
Top: 3 mm
Cylinder: 3 mm
Bottom: 3 mm

Distance from outlet to ground: 250 mm
Outer diameter tank: 703 mm
Cylinder height: 750 mm
Total height of tank: 1.760 mm
Empty weight tank: 90

SKU: 375608

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Nytillverkad
Arbetstryck i tank: ATM – atmospheric
Finish rostfritt stål: 2b
Konfiguration: single-skin
Max. arbetstemperatur: 80 °C
Maximal densitet för produkten: 1200
Min. arbetstemperatur: -10 °C
Mobil tank: Nej
Övrig information: delivered with food certificate; article price without agitator; choice of 2 different types of agitators; see options; (The article can also be purchased without options);
Övrig information2: Ra=<0.8µm
Omrörare: Nej
Ra innersvets: 0,80
Tankens form: cylindrical
Total urtappning: Yes
Typ av botten: conical 10 °
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 300

Utrustning

Fläns för omrörare: Ja
Märkskylt: Ja
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 40 mm
Teknisk ritning finns: Ja
Utloppstyp: DIN11851

Översikt material
Material: Syrafast 316
Fixeringspunkt(er): RVS 304

Dimensioner av tank
Cylinderhöjd: 750 mm
Mått utlopp till marken: 250 mm
Total höjd: 1.760 mm
Ytterdiameter: 703 mm

Omrörare
Kraft (kW): 0,37
Position motor: at the top
Typ av omrörare: propeller agitator
Varvtal: 1.410
Spänning (Volt): three-phase

Tjocklek på tank
Botten: 3 mm
Cylinder: 3 mm
Topp: 3 mm

Mer
Isolerad: Nej
Vikt: 90