

## 300 liter tank i Syrafast 316



## 107 000 SEK /st exkl moms

item available on order

**Article type:** brand new mixing tank - type VC-SLA

**Additional information:** delivered with food certificate; *article price without agitator; choice of 2 different types of agitators; see options; (The article can also be purchased without options);* Ra=<0.8µm

**Volumetric volume (L):** 300 L

**Max. density P (kg/m<sup>3</sup>):** 1.200

**Ra inner weld:** 0,80

**Finish stainless steel:** 2b

**Pressure in tank:** ATM - atmosferic

**Max. temperature (°C):** 80 °C

**Min. temperature (°C):** -10 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** single-skin

**Heat exchanger:** no

**Insulation:** no

**Mobile tank:** no

**Top type:** half hinging lid °

**Shape of tank:** cylindrical

**Bottom type:** conical 10 °

**Total discharge:** yes

**Fixation points:** 3 non adjustable feet

**Valve:** RVS 316L

**Fixation point(s):** RVS 304

**Suitable for food industry:** yes

**Documents included:** yes, optional

**Technical drawing included:** yes

**Registration plate on the tank:** yes

**Flange for agitator:** yes

**CIP spray ball:** no, optional  
**Tank outlet:** inside Ø 40 mm  
**Outlet type:** DIN11851

**Total outlet valve:** no, optional  
**Agitator:** no, optional  
**Agitator type:** propeller agitator  
**Position engine:** at the top  
**Number of revolutions:** 1.410

**Power:** 0,37  
**Voltage:** three-phase  
**Agitator type 2:** propeller agitator  
**Position engine:** at the top  
**Number of revolutions:** 750

**Power:** 0,25  
**Voltage:** three-phase  
**Top:** 3 mm  
**Cylinder:** 3 mm  
**Bottom:** 3 mm

**Distance from outlet to ground:** 250 mm  
**Outer diameter tank:** 703 mm  
**Cylinder height:** 750 mm  
**Total height of tank:** 1.760 mm  
**Empty weight tank:** 90

**SKU:** 375608

## Mer information

### Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Nyttillverkad

Arbetsstryck i tank: ATM – atmosferic

Finish rostfritt stål: 2b

Konfiguration: single-skin

Max. arbetstemperatur: 80 °C

Maximal densitet för produkten: 1200

Min. arbetstemperatur: -10 °C

Mobil tank: Nej

Övrig information: delivered with food certificate; article price without agitator; choice of 2 different types of agitators; see options; (The article can also be purchased without options);

Övrig information2: Ra=<0.8µm

Omrörare: Nej

Ra innersvets: 0,80

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical 10 °

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 300

### Utrustning

Fläns för omrörare: Ja

Märkskylt: Ja

Livsmedelsklassad: Ja

Tankutlopp: inside Ø 40 mm

Teknisk ritning finns: Ja

Utloppstyp: DIN11851



## Översikt material

Material: Syrafast 316

Fixeringspunkt(er): RVS 304

## Dimensioner av tank

Cylinderhöjd: 750 mm

Mått utlopp till marken: 250 mm

Total höjd: 1.760 mm

Ytterdiameter: 703 mm

## Omrörare

Kraft (kW): 0,37

Position motor: at the top

Typ av omrörare: propeller agitator

Varvtal: 1.410

Spänning (Volt): three-phase

## Tjocklek på tank

Botten: 3 mm

Cylinder: 3 mm

Topp: 3 mm

## Mer

Isolerad: Nej

Vikt: 90