300 liter tank i Rostfritt 304



29 000 SEK /st exkl moms

Article type: second-hand storage tank
Additional information: The wheels, manhole flange and closures for the manhole are missing, a new lid with closures = €1900; Special flange on the outlet, we can adjust this to a connection of your choice, this costs €474. We can modify the tank for you, contact us without obligation for your quote.
Volumetric volume (L): 300 L
Ra inner weld: 0,80
Pressure in tank: pressure and vacuum

Design pressure (Bar): 3 Bar
Max. pressure (Bar): 4 Bar
Min. pressure (Bar): -1 Bar

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. temperature (°C): 132 °C
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

Top type: dished
Shape of tank: cylindrical
Bottom type: conical
Bottom outlet: yes
Total discharge: yes

Fixation points: 4 non adjustable feet
Manway(s): RVS 304
Gasket manway(s): unknown
Fixation point(s): RVS 304
Suitable for food industry: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Number of manways: 1

Position of manway: at the top
Tank outlet: inside Ø 50 mm
Agitator: no
Top: 5 mm
Cylinder: 3 mm

Bottom: 5 mm
Distance from outlet to ground: 290 mm
Outer diameter tank: 720 mm
Cylinder height: 650 mm
Total height of tank: 1.430 mm

Total outer width: 762 mm

Total outer length: 780 mm

SKU: 433373

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Designtryck för tanken: 3 Bar
Konfiguration: single-skin
Max. arbetstemperatur: 132 °C
Mobil tank: Nej
Övrig information: The wheels, manhole flange and closures for the manhole are missing, a new lid with closures = €1900; Special flange on the outlet, we can adjust this to a connection of your choice, this costs
Övrig information2: €474. We can modify the tank for you, contact us without obligation for your quote.
Omrörare: Nej
Övertryck: 4 Bar
Ra innersvets: 0,80
Tankens form: cylindrical
Total urtappning: Yes
Typ av botten: conical
Undertryck (vakuum): -1 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 300

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 50 mm
Teknisk ritning finns: Nej

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Översikt material
Material: Rostfritt 304
Fixeringspunkt(er): RVS 304

Dimensioner av tank
Cylinderhöjd: 650 mm
Mått utlopp till marken: 290 mm
Total höjd: 1.430 mm
Ytterdiameter: 720 mm

Tjocklek på tank
Botten: 5 mm
Cylinder: 3 mm
Topp: 5 mm

Mer
Isolerad: Nej

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se