3000 liter tank i Rostfritt 304



149 000 SEK /st exkl moms

Article type: second-hand pressure tank
Additional information: Full vacuum -1 bar; we can't give any guarantees about the heating/cooling jacket
Volumetric volume (L): 3.000 L
Max. density P (kg/m³): 1
Pressure in tank: vacuum

Max. pressure (Bar): 0,49 Bar
Min. pressure (Bar): -1 Bar
Max. temperature (°C): 98 °C
Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: insulated with heat-exchanger

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Heat exchanger: yes
Insulation: yes
Mobile tank: no
Top type: dished

Shape of tank: cylindrical
Bottom type: dished
Total discharge: yes
Fixation points: 3 adjustable feet
Type of HE on the cylinder: half pipe welded onto the outside of the innertank

Water pressure HE: 3 Bar
Working temperature HE cylinder: 98 °C
Type of HE on the bottom: half pipe welded onto the outside of the innertank
Water pressure HE: 3 Bar
Working temperature HE bottom: 98 °C

Heat exchanger: RVS 304
Insulation material: rockwool
Manway(s): RVS 304
Gasket manway(s): unknown
Fixation point(s): RVS 304

Suitable for food industry: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no

Number of manways: 1
Position of manway: at the top
Height manhole 1 (mm): 400 mm
Tank outlet: inside Ø 32 mm
Total outlet valve: no

Agitator: no
Top: 6 mm
Cylinder: 6 mm
Bottom: 6 mm

Insulation body: yes

Insulation bottom/sides: yes
finish of the outer jacket: welded
Insulation thickness: 50
Internal diameter tank: 1.500 mm
Distance from outlet to ground: 1.000 mm

Outer diameter tank: 1.600 mm
Cylinder height: 1.900 mm
Total height of tank: 3.600 mm

SKU: 381770

Mer information

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: vacuum
Konfiguration: insulated with heat-exchanger
Max. arbetstemperatur: 98 °C
Maximal densitet för produkten: 1
Mobil tank: Nej
Övrig information: Full vacuum -1 bar; we can’t give any guarantees about the heating/cooling jacket
Omrörare: Nej
Övertryck: 0,49 Bar
Tankens form: cylindrical
Total urtappning: Yes
Typ av botten: dished
Undertryck (vakuum): -1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 3000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 32 mm
Teknisk ritning finns: Nej
Utloppsventil: Nej

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): RVS 304
Isoleringsmaterial: Rockwool

Dimensioner av tank

Cylinderhöjd: 1.900 mm
Invändig diameter: 1.500 mm
Mått utlopp till marken: 1.000 mm
Total höjd: 3.600 mm
Ytterdiameter: 1.600 mm

Värmeväxlare

Arbetstemperatur värmeväxlare cylinder: 98 °C
Arbetstemperatur värmeväxlare botten: 98 °C
Typ av värmeväxlare på cylinder: half pipe welded onto the outside of the innertank
Typ av värmeväxlare på botten: half pipe welded onto the outside of the innertank
Vattentryck värmeväxlare: 3 Bar
Vattentryck värmeväxlare botten: 3 Bar

Tjocklek på tank

Botten: 6 mm
Cylinder: 6 mm
Topp: 6 mm

Tjocklek på ytterbeklädnad och isolering

Finish utvändig mantel: welded
Isolering botten/gavlar: Ja
Isolering mantel: Ja
Isoleringsmaterial: Rockwool

Mer

Värmeväxlare: RVS 304
Isoleringstjocklek OW: 50
Isolerad: Ja

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se