

## 3000 liter tank i Rostfritt 304



**150,000,00 kr /st exkl moms**

**Article type:** second-hand pressure tank

**Additional information:** Full vacuum -1 bar; we can't give any guarantees about the heating/cooling jacket

**Volumetric volume (L):** 3.000 L

**Max. density P (kg/m<sup>3</sup>):** 1

**Pressure in tank:** vacuum

**Max. pressure (Bar):** 0,49 Bar

**Min. pressure (Bar):** -1 Bar

**Max. temperature (°C):** 98 °C

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical



**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Top type:** dished

**Shape of tank:** cylindrical

**Bottom type:** dished

**Total discharge:** yes

**Fixation points:** 3 adjustable feet

**Type of HE on the cylinder:** half pipe welded onto the outside of the innertank

**Water pressure HE:** 3 Bar

**Working temperature HE cylinder:** 98 °C

**Type of HE on the bottom:** half pipe welded onto the outside of the innertank

**Water pressure HE:** 3 Bar

**Working temperature HE bottom:** 98 °C

**Heat exchanger:** RVS 304

**Insulation material:** rockwool

**Manway(s):** RVS 304

**Gasket manway(s):** unknown

**Fixation point(s):** RVS 304

**Suitable for food industry:** yes

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** no

**Flange for agitator:** no

**Number of manways:** 1

**Position of manway:** at the top

**Height manhole 1 (mm):** 400 mm

**Tank outlet:** inside Ø 32 mm

**Total outlet valve:** no

**Agitator:** no

**Top:** 6 mm

**Cylinder:** 6 mm

**Bottom:** 6 mm

**Insulation body:** yes

**Insulation bottom/sides:** yes

**finish of the outer jacket:** welded

**Insulation thickness:** 50

**Internal diameter tank:** 1.500 mm

**Distance from outlet to ground:** 1.000 mm

**Outer diameter tank:** 1.600 mm

**Cylinder height:** 1.900 mm

**Total height of tank:** 3.600 mm

**SKU:** 21000

---

Mer information

## Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 98 °C

Maximal densitet för produkten: 1

Mobil tank: Nej

Övrig information: Full vacuum -1 bar; we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Övertryck: 0,49 Bar

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: dished

Undertryck (vakuum): -1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 3000

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Livsmedelsklassad: Ja

Tankutlopp: inside Ø 32 mm

Teknisk ritning finns: Nej

Utloppsventil: Nej

## Översikt material

Material: Rostfritt 304

Fixeringspunkt(er): RVS 304

Isoleringsmaterial: Rockwool

## Dimensioner av tank

Cylinderhöjd: 1.900 mm

Invändig diameter: 1.500 mm

Mått utlopp till marken: 1.000 mm

Total höjd: 3.600 mm

Ytterdiameter: 1.600 mm

## Värmeväxlare

Arbetstemperatur värmeväxlare cylinder: 98 °C

Arbetstemperatur värmeväxlare botten: 98 °C

Typ av värmeväxlare på cylinder: half pipe welded onto the outside of the innertank

Typ av värmeväxlare på botten: half pipe welded onto the outside of the innertank

Vattentryck värmeväxlare: 3 Bar

Vattentryck värmeväxlare botten: 3 Bar

## Tjocklek på tank

Botten: 6 mm

Cylinder: 6 mm

Topp: 6 mm

## Tjocklek på ytterbeklädnad och isolering

Finish utvändig mantel: welded

Isolering botten/gavlar: Ja

Isolering mantel: Ja

Isoleringsmaterial: Rockwool

**Mer**

Värmeväxlare: RVS 304

Isoleringstjocklek OW: 50

Isolerad: Ja