

3000 liter tank i Rostfritt 304



112 000 SEK /st exkl moms

Additional information: Fats; 3 legs, stainless steel 304 welded to a stainless steel 304 frame; 1 DN 80 connection (11851) next to the tank outlet; 1 circular opening, approx. 48 mm in diameter, in the manhole cover; manhole cover temporarily sealed; some residues of previous content

Volumetric volume (L): 3.000 L



Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Position of manway: headside

Outlet of tank: DN50 DIN 11851
Agitator: yes
Number of revolutions: 1.430
Power: 3
Internal diameter tank: 1.430 mm

Cylinder height: 1.800 mm
Total height of tank: 3.250 mm

SKU: 707491

Mer information



Beskrivning av produkt

Material: Rustfritt stål 304

Modell: Vertikal

Nyttillverkad/Begagnad: Brukt

Arbetsstryck i tank: ATM – atmosfærisk

Konfiguration: enkelthudet

Mobil tank: Nei, det er det ikke.

Övrig information: Fats; 3 legs, stainless steel 304 welded to a stainless steel 304 frame; 1 DN 80 connection (11851) next to the tank outlet; 1 circular opening, approx. 48 mm in diameter, in the manhole cover;

Övrig information2: manhole cover temporarily sealed; some residues of previous content; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Nei, det er det ikke.

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 3000

Utrustning

Dokument finns: Nei, det er det ikke.

Fläns för omrörare: Nei

Märkskylt: Nei, det er det ikke.

Teknisk ritning finns: Nei, det er det ikke.

Översikt material

Material: Rustfritt stål 304

Dimensioner av tank

Cylinderhöjd: 1 800 mm

Invändig diameter: 1 430 mm

Total höjd: 3 250 mm

**Omrörare**

Kraft (kW): 3

Varvtal: 1.430

Mer

Isolerad: Nei