3000 liter tank i Rostfritt 304



45 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: Ex-milk cooling tank. Cooling unit not available; cooling jacket no longer operational. The tank has a few small dents and scratches. Please view the pictures closely.; we can't give any guarantees about the agitator
Volumetric volume (L): 3.000 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)

Model: horizontal
Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Top type: dished
Shape of tank: cylindrical
Bottom type: dished
Total discharge: no
Fixation points: 4 adjustable feet

Insulation material: PUR
Outer jacket (ornamental wall): RVS 304
Manway(s): RVS 304
Gasket manway(s): unknown
Valve: RVS 304

Gasket shut-off valve (mat): unknown
Fixation point(s): RVS 304
Wet parts agitator(s): SS AISI 304 (V2A)
Suitable for food industry: yes
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Number of manways: 1
Position of manway: at the top

Height manhole 1 (mm): 442 mm
Tank outlet: inside Ø 50 mm
Outlet type: DIN11851
Outlet of tank: DN50
Agitator: yes

Agitator type: propeller agitator
Position engine: at the top
Number of revolutions: 35
Power: 0,18
Voltage: 230/400 V - three-phase

Current: 1.04/0.6
finish of the outer jacket: welded
Internal diameter tank: 1.330 mm
Distance from outlet to ground: 360 mm

Outer diameter tank: 1.414 mm

Cylinder height: 2.360 mm
Feet height: 350 mm
Total height of tank: 2.170 mm
Total outer width: 1.430 mm
Total outer length: 3.150 mm

Empty weight tank: 425

SKU: 708814

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Rostfritt 304
Modell: Horisontell
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated
Mobil tank: Nej
Övrig information: Ex-milk cooling tank. Cooling unit not available; cooling jacket no longer operational. The tank has a few small dents and scratches. Please view the pictures closely.; we can’t give any guarantees
Övrig information2: about the agitator
Omrörare: Ja
Tankens form: cylindrical
Total urtappning: Nej
Typ av botten: dished
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 3000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 50 mm
Teknisk ritning finns: Nej
Utloppstyp: DIN11851

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): RVS 304
Isoleringsmaterial: PUR
Material vätskeberörd del på omrörare: SS AISI 304 (V2A)
Ytterbeklädnad: RVS 304

Dimensioner av tank

Cylinderhöjd: 2.360 mm
Höjd på fötter: 350 mm
Invändig diameter: 1.330 mm
Mått utlopp till marken: 360 mm
Total höjd: 2.170 mm
Ytterdiameter: 1.414 mm

Omrörare

Kraft (kW): 0.18kW
Position motor: at the top
Typ av omrörare: propeller agitator
Varvtal: 35rpm
Spänning (Volt): 230/400 V – three-phase

Tjocklek på ytterbeklädnad och isolering

Finish utvändig mantel: welded
Isoleringsmaterial: PUR

Mer

Isolerad: Ja
Vikt: 425