

3000 liter tank i Rostfritt 304



46 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: Ex-milk cooling tank. Cooling unit not available; cooling jacket no longer operational. The tank has a few small dents and scratches. Please view the pictures closely.; we can't give any guarantees about the agitator

Volumetric volume (L): 3.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: horizontal

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no



Top type: dished
Shape of tank: cylindrical
Bottom type: dished
Total discharge: no
Fixation points: 4 adjustable feet

Insulation material: PUR
Outer jacket (ornamental wall): RVS 304
Manway(s): RVS 304
Gasket manway(s): unknown
Valve: RVS 304

Gasket shut-off valve (mat): unknown
Fixation point(s): RVS 304
Wet parts agitator(s): SS AISI 304 (V2A)
Suitable for food industry: yes
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Number of manways: 1
Position of manway: at the top

Height manhole 1 (mm): 442 mm
Tank outlet: inside Ø 50 mm
Outlet type: DIN11851
Outlet of tank: DN50
Agitator: yes

Agitator type: propeller agitator
Position engine: at the top
Number of revolutions: 35
Power: 0,18
Voltage: 230/400 V - three-phase

Current: 1.04/0.6
finish of the outer jacket: welded
Internal diameter tank: 1.330 mm
Distance from outlet to ground: 360 mm

Outer diameter tank: 1.414 mm

Cylinder height: 2.360 mm

Feet height: 350 mm

Total height of tank: 2.170 mm

Total outer width: 1.430 mm

Total outer length: 3.150 mm

Empty weight tank: 425

SKU: 708814

Mer information



Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Horisontell

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: insulated

Mobil tank: Nej

Övrig information: Ex-milk cooling tank. Cooling unit not available; cooling jacket no longer operational. The tank has a few small dents and scratches. Please view the pictures closely.; we can't give any guarantees

Övrig information2: about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Nej

Typ av botten: dished

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 3000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Livsmedelsklassad: Ja

Tankutlopp: inside Ø 50 mm

Teknisk ritning finns: Nej

Utloppstyp: DIN11851

Översikt material

Material: Rostfritt 304

Fixeringspunkt(er): RVS 304

Isoleringsmaterial: PUR

Material vätskeberörd del på omrörare: SS AISI 304 (V2A)

Ytterbeklädnad: RVS 304



Dimensioner av tank

Cylinderhöjd: 2.360 mm

Höjd på fötter: 350 mm

Invändig diameter: 1.330 mm

Mått utlopp till marken: 360 mm

Total höjd: 2.170 mm

Ytterdiameter: 1.414 mm

Omrörare

Kraft (kW): 0.18kW

Position motor: at the top

Typ av omrörare: propeller agitator

Varvtal: 35rpm

Spänning (Volt): 230/400 V – three-phase

Tjocklek på ytterbeklädnad och isolering

Finish utvändig mantel: welded

Isoleringsmaterial: PUR

Mer

Isolerad: Ja

Vikt: 425