

3000 liter tank i Rostfritt 304



106 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Volumetric volume (L): 3.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes

Insulation: yes

Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: conical

Bottom outlet: yes

Total discharge: yes

Fixation points: 3 adjustable feet

Type of HE on the cylinder: half pipe welded onto the outside of the innertank

Position HE: the complet cilinder

Type of HE on the bottom: half pipe welded onto the outside of the innertank

Manway(s): RVS 304

Gasket manway(s): unknown

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 1

Position of manway: at the top

Height manhole 1 (mm): 350 mm x H 440 mm

Hinged lid: yes

Tank outlet: inside Ø 50 mm

Agitator: yes

Agitator type: propeller agitator

Position engine: at the top

Power: 1,50

Voltage: 380 V - three-phase

Current: 3,70

Distance from outlet to ground: 700 mm

Outer diameter tank: 1.700 mm

Cylinder height: 1.650 mm

Total height of tank: 3.600 mm

Empty weight tank: 950

SKU: 438599

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Mobil tank: Nej

Övrig information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 3000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 50 mm
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): RVS 304

Dimensioner av tank

Cylinderhöjd: 1.650 mm
Mått utlopp till marken: 700 mm
Total höjd: 3.600 mm
Ytterdiameter: 1.700 mm

Värmeväxlare

Position värmeväxlare: the complet cilinder
Typ av värmeväxlare på cylinder: half pipe welded onto the outside of the innertank
Typ av värmeväxlare på botten: half pipe welded onto the outside of the innertank

Omrörare

Kraft (kW): 1,50
Position motor: at the top
Typ av omrörare: propeller agitator
Spänning (Volt): 380 V - three-phase

Mer

Isolerad: Ja
Vikt: 950