

## 3000 liter tank i Rostfritt 304



**106 000 SEK /st exkl moms**

**Article type:** second-hand mixing tank

**Additional information:** we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

**Volumetric volume (L):** 3.000 L

**Pressure in tank:** ATM - atmosferic

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Top type:** conical

**Shape of tank:** cylindrical

**Bottom type:** conical

**Bottom outlet:** yes

**Total discharge:** yes

**Fixation points:** 3 adjustable feet

**Type of HE on the cylinder:** half pipe welded onto the outside of the innertank

**Position HE:** the complet cilinder

**Type of HE on the bottom:** half pipe welded onto the outside of the innertank

**Manway(s):** RVS 304

**Gasket manway(s):** unknown

**Fixation point(s):** RVS 304

**Suitable for food industry:** yes

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** no

**Flange for agitator:** no

**Number of manways:** 1

**Position of manway:** at the top

**Height manhole 1 (mm):** 350 mm x H 440 mm

**Hinged lid:** yes

**Tank outlet:** inside Ø 50 mm

**Agitator:** yes

**Agitator type:** propeller agitator

**Position engine:** at the top

**Power:** 1,10

**Voltage:** 400 V - three-phase

**Current:** 2,95

**Distance from outlet to ground:** 700 mm

**Outer diameter tank:** 1.700 mm

**Cylinder height:** 1.650 mm

**Total height of tank:** 3.000 mm

**Empty weight tank:** 970

**SKU:** 294739

## Mer information

### Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Mobil tank: Nej

Övrig information: we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 3000

## Utrustning

Dokument finns: Nej  
Fläns för omrörare: Nej  
Märkskylt: Nej  
Livsmedelsklassad: Ja  
Tankutlopp: inside Ø 50 mm  
Teknisk ritning finns: Nej

## Översikt material

Material: Rostfritt 304  
Fixeringspunkt(er): RVS 304

## Dimensioner av tank

Cylinderhöjd: 1.650 mm  
Mått utlopp till marken: 700 mm  
Total höjd: 3.000 mm  
Ytterdiameter: 1.700 mm

## Värmeväxlare

Position värmeväxlare: the complet cilinder  
Typ av värmeväxlare på cylinder: half pipe welded onto the outside of the innertank  
Typ av värmeväxlare på botten: half pipe welded onto the outside of the innertank

## Omrörare

Kraft (kW): 1,10  
Position motor: at the top  
Typ av omrörare: propeller agitator  
Spänning (Volt): 400 V - three-phase

## Mer

Isolerad: Ja  
Vikt: 970