

3000 liter tank i Syrafast 316



71 000 SEK /st exkl moms

Additional information: Small dents in the double jacket; remnants of the cut-open insulating jacket on the outside of the tank (see photos); some residues of previous content; pipe end cut flush

Volumetric volume (L): 3.000 L

Pressure in tank: ATM - atmospheric



Max. temperature (°C): 150 °C
Material wet parts: SS AISI 316 (V4A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

Total discharge: yes
Max Overpressure: 2 Bar
Max. working temperature: 150 °C
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: 50
Internal diameter tank: 1.690 mm

Outer diameter tank: 1.740 mm
Cylinder height: 1.170 mm
Total height of tank: 2.400 mm

SKU: 705814

Mer information



Beskrivning av produkt

Material: Syrefast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Brukt

Arbetsstryck i tank: ATM – atmosfærisk

Konfiguration: enkelthudet

Max. arbetstemperatur: 150 °C

Mobil tank: Nei, det er det ikke.

Övrig information: Small dents in the double jacket; remnants of the cut-open insulating jacket on the outside of the tank (see photos); some residues of previous content; pipe end cut flush

Omrörare: Nei

Total urtappning: Ja

Uppvärmning/kylning: Nei, det er det ikke.

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 3000

Utrustning

Dokument finns: Nei, det er det ikke.

Fläns för omrörare: Nei

Märkskylt: Ja

Teknisk ritning finns: Nei, det er det ikke.

Översikt material

Material: Syrefast 316

Dimensioner av tank

Cylinderhöjd: 1 170 mm

Invändig diameter: 1690 mm

Total höjd: 2 400 mm

Ytterdiameter: 1 740 mm

Mer

Isolerad: Nei

