

3000 liter tank i Syrafast 316



83 000 SEK /st exkl moms

Additional information: Manhole diameter approx. 520 mm (manhole cover mounting incomplete); piping inside the tank; outlet flange DN 200 (with flanged valve); some residues of previous content

Volumetric volume (L): 3.000 L

Pressure in tank: ATM - atmospheric



Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Internal diameter tank: 1.420 mm

Outer diameter tank: 1.550 mm

Cylinder height: 1.800 mm

Total height of tank: 3.150 mm

SKU: 704866

Mer information



Beskrivning av produkt

Material: Syrefast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Brukt

Arbetsstryck i tank: ATM – atmosfærisk

Konfiguration: isolert

Mobil tank: Nei, det er det ikke.

Övrig information: Manhole diameter approx. 520 mm (manhole cover mounting incomplete); piping inside the tank; outlet flange DN 200 (with flanged valve); some residues of previous content

Omrörare: Nei

Total urtappning: Ja

Uppvärmning/kylning: Nei, det er det ikke.

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 3000

Utrustning

Dokument finns: Nei, det er det ikke.

Fläns för omrörare: Nei

Märkskylt: Ja

Teknisk ritning finns: Nei, det er det ikke.

Översikt material

Material: Syrefast 316

Dimensioner av tank

Cylinderhöjd: 1 800 mm

Invändig diameter: 1 420 mm

Total höjd: 3 150 mm

Ytterdiameter: 1 550 mm

Mer

Isolerad: Ja

