3000 liter tank i Syrafast 316



109 000 SEK /st exkl moms

Additional information: Support ring made of stainless steel 304; manhole diameter approx. 410 mm
Volumetric volume (L): 3.000 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 4 Bar

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 100 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Documents included: no
Technical drawing included: no

Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside
Outlet of tank: 48
Agitator: yes

Number of revolutions: 119
Power: 1,10
Internal diameter tank: 1.390 mm
Cylinder height: 1.630 mm
Total height of tank: 3.450 mm

SKU: 453113

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single-skin
Max. arbetstemperatur: 100 °C
Mobil tank: Nej
Övrig information: Support ring, Aisi 304; Manhole diameter approx. 410 mm; we can't give any guarantees about the agitator
Omrörare: Ja
Övertryck: 4 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 3000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.630 mm
Invändig diameter: 1.390 mm
Total höjd: 3.450 mm

Omrörare
Kraft (kW): 1,10
Varvtal: 119

Mer
Isolerad: Nej