

## 3000 liter tank i Syrafast 316



**56 000 SEK /st exkl moms**

**Additional information:** Cip-tank; Several pipes inside the tank (see photos)

**Volumetric volume (L):** 3.000 L

**Pressure in tank:** ATM - atmosferic

**Max. temperature (°C):** 80 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** single-skin

**Heat exchanger:** no

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** in the bottom

**Outlet of tank:** flange DN150

**Cylinder:** 3 mm

**Bottom:** 4 mm

**Internal diameter tank:** 1.500 mm

**Cylinder height:** 1.700 mm

**Total height of tank:** 2.900 mm

**SKU:** 278884

Mer information



## Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Max. arbetstemperatur: 80 °C

Mobil tank: Nej

Övrig information: Cip-tank; Several pipes inside the tank (see photos)

Omrörare: Nej

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 3000

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

## Översikt material

Material: Syrafast 316

## Dimensioner av tank

Cylinderhöjd: 1.700 mm

Invändig diameter: 1.500 mm

Total höjd: 2.900 mm

## Tjocklek på tank

Botten: 4 mm

Cylinder: 3 mm

**Mer**

Isolerad: Nej

---