3000 liter tank i Syrafast 316



119 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: we can't give any guarantees about the agitator
Volumetric volume (L): 3.000 L
Pressure in tank: ATM - atmosferic

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. temperature (°C): 60 °C

Min. temperature (°C): 10 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Top type: conical
Shape of tank: cylindrical
Bottom type: conical

Total discharge: yes
Fixation points: 4 adjustable feet
Manway(s): RVS 316
Gasket manway(s): unknown
Fixation point(s): RVS 304

Wet parts agitator(s): SS AISI 304 (V2A)
Suitable for food industry: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes

Flange for agitator: no
Number of manways: 1
Position of manway: at the top
Hinged lid: yes
Agitator: yes

Agitator type: propeller agitator
Position engine: at the top
Power: 3
Outer diameter tank: 1.400 mm
Cylinder height: 2.000 mm

Feet height: 1.200 mm

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Total height of tank: 3.900 mm

SKU: 411614

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmospheric
Konfiguration: single-skin
Max. arbetstemperatur: 60 °C
Min. arbetstemperatur: 10 °C
Mobil tank: Nej
Övrig information: we can't give any guarantees about the agitator
Omrörare: Ja
Tankens form: cylindrical
Total urtappning: Yes
Typ av botten: conical
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 3000

Utrustning
Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Livsmedelsklassad: Ja
Teknisk ritning finns: Nej

Översikt material
Material: Syrafast 316
Fixeringspunkt(er): RVS 304
Material vätskeberörd del på omrörare: SS AISI 304 (V2A)

Dimensioner av tank
Cylinderhöjd: 2.000 mm
Höjd på fötter: 1.200 mm
Total höjd: 3.900 mm
Ytterdiameter: 1.400 mm

Omrörare
Kraft (kW): 3
Position motor: at the top
Typ av omrörare: propeller agitator

Mer
Isolerad: Nej