3000 liter tank i Syrafast 316



92 000 SEK /st exkl moms

Additional information: chemistry; External steel parts sandblasted and primed; upper bottom can also be heated/cooled; some residues of previous content
Volumetric volume (L): 3.000 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 316 (V4A)

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Model: vertical

Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no
Total discharge: yes

Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Documents included: no
Technical drawing included: no
Registration plate on the tank: no

Flange for agitator: no
Position of manway: headside
Outlet of tank: 135
Agitator: yes
Power: 2,20

Internal diameter tank: 1.400 mm
Outer diameter tank: 1.450 mm
Cylinder height: 1.650 mm
Total height of tank: 4.300 mm

SKU: 389867

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: single jacketed with heat-exchanger
Mobil tank: Nej
Övrig information: chemistry; mild steel parts outside sandblasted and primed; upper bottom heat-/coolable as well; some residues of previous content; we can't give any guarantees about the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 3000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.650 mm
Invändig diameter: 1.400 mm
Total höjd: 4.300 mm
Ytterdiameter: 1.450 mm

Omrörare

Kraft (kW): 2,20

Mer
Isolerad: Nej