

## 30000 liter tank i Rostfritt 304



**196 000 SEK /st exkl moms**

**Additional information:** Dairy; Manhole approx. 345 x 445 mm; height-adjustable dome screws of the feet missing; bump at the insulation jacket; manhole cover is missing; pipe end cut flush

**Volumetric volume (L):** 30.000 L

**Pressure in tank:** ATM - atmosferic

**Max. temperature (°C):** 80 °C  
**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical  
**Configuration:** insulated  
**Heat exchanger:** no  
**Insulation:** yes  
**Mobile tank:** no

**Total discharge:** yes  
**Documents included:** no  
**Technical drawing included:** no  
**Registration plate on the tank:** yes  
**Flange for agitator:** no

**Position of manway:** cylinder  
**Outlet of tank:** 48  
**Agitator:** yes  
**Number of revolutions:** 20 / 41  
**Power:** 1.2 / 2.2

**Internal diameter tank:** 2.880 mm  
**Outer diameter tank:** 3.020 mm  
**Total height of tank:** 6.700 mm

**SKU:** 486245

Mer information



## Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated

Max. arbetstemperatur: 80 °C

Mobil tank: Nej

Övrig information: Dairy; Manhole approx. 345 x 445 mm; height-adjustable screws of the feet are missing; bump at the insulation jacket; manhole cover is missing; pipe end cut flush; we can't give any guarantees about

Övrig information2: the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 30000

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

## Översikt material

Material: Rostfritt 304

## Dimensioner av tank

Invändig diameter: 2.880 mm

Total höjd: 6.700 mm

Ytterdiameter: 3.020 mm

**Omrörare**

Kraft (kW): 1.2 / 2.2

Varvtal: 20 / 41

**Mer**

Isolerad: Ja