30000 liter tank i Rostfritt 304



197 000 SEK /st exkl moms

Additional information: Manhole approx. 345 x 445 mm; height-adjustable dome screws of the feet missing; bump at the insulation jacket; manhole cover is missing; pipe end cut flush
Volumetric volume (L): 30.000 L
Pressure in tank: ATM - atmosferic
Max. temperature (°C): 80 °C

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no

Total discharge: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no

Position of manway: cylinder
Outlet of tank: 48
Agitator: yes
Number of revolutions: 20 / 41
Power: 1.2 / 2.2

Internal diameter tank: 2.880 mm
Outer diameter tank: 3.020 mm
Total height of tank: 6.700 mm

SKU: 486245

Mer information

Beskrivning av produkt

Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated
Max. arbetstemperatur: 80 °C
Mobil tank: Nej
Övrig information: Dairy; Manhole approx. 345 x 445 mm; height-adjustable screws of the feet are missing; bump at the insulation jacket;manhole cover is missing;pipe end cut flush; we can't give any guarantees about
Övrig information2: the agitator
Omrörare: Ja
Total urtappning: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 30000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Invändig diameter: 2.880 mm
Total höjd: 6.700 mm
Ytterdiameter: 3.020 mm

Omrörare
Kraft (kW): 1.2 / 2.2
Varvtal: 20 / 41

Mer
Isolerad: Ja