30000 liter tank i Rostfritt 304



294 000 SEK /st exkl moms

Article type: second-hand storage tank
Additional information: double jacket for leak detection (system for detection not included)
Volumetric volume (L): 30.000 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304L (V2A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Top type: conical
Shape of tank: cylindrical
Bottom type: conical
Total discharge: yes
Fixation points: 4 adjustable feet

Outer jacket (ornamental wall): RVS 304L
Manway(s): RVS 304L
Gasket manway(s): unknown
Fixation point(s): RVS 304L
Suitable for food industry: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Number of manways: 1

Position of manway: at the top
Height manhole 1 (mm): 500 mm
Tank outlet: inside Ø 50 mm
Agitator: no, optional
Distance from outlet to ground: 400 mm

Outer diameter tank: 3.850 mm
Cylinder height: 2.600 mm
Total height of tank: 4.600 mm
Empty weight tank: 4.500

SKU: 482863

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmospheric
Konfiguration: single-skin
Mobil tank: Nej
Övrig information: double jacket for leak detection (system for detection not included)
Omrörare: Nej
Tankens form: cylindrical
Total urtappning: Yes
Typ av botten: conical
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304L (V2A)
Volym i liter: 30000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 50 mm
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): RVS 304L
Ytterbeklädnad: RVS 304L

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Dimensioner av tank

Cylinderhöjd: 2.600 mm
Mått utlopp till marken: 400 mm
Total höjd: 4.600 mm
Ytterdiameter: 3.850 mm

Mer

Isolerad: Nej
Vikt: 4.500