

## 30000 liter tank i Rostfritt 304



**224,000,00 kr /st exkl moms**

**Article type:** second-hand mixing tank

**Additional information:** we can't give any guarantees about the agitator

**Volumetric volume (L):** 30.000 L

**Pressure in tank:** ATM - atmosferic

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** single-skin

**Heat exchanger:** no

**Insulation:** no



**Mobile tank:** no

**Top type:** conical

**Shape of tank:** cylindrical

**Bottom type:** conical

**Total discharge:** yes

**Fixation points:** 3 non adjustable feet

**Manway(s):** RVS 304

**Fixation point(s):** RVS 304

**Suitable for food industry:** yes

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** no

**Flange for agitator:** no

**Number of manways:** 2

**Position of manway:** at the top

**Height manhole 1 (mm):** 500 mm

**Position 2nd manway:** cylinder

**Height manhole 2 (mm):** 340 x 430 mm

**Tank outlet:** inside Ø 100 mm

**Outlet type:** DIN11851

**Agitator:** yes

**Agitator type:** anchor

**Position engine:** at the top

**Number of revolutions:** 35

**Power:** 9,50

**Voltage:** three-phase

**Top:** 3 mm

**Cylinder:** 3 mm

**Bottom:** 4 mm

**Distance from outlet to ground:** 700 mm

**Outer diameter tank:** 3.000 mm

**Cylinder height:** 4.550 mm

**Total height of tank:** 7.000 mm

**Empty weight tank:** 2.000

**SKU:** 565892

## Mer information

### Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Mobil tank: Nej

Övrig information: we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 30000



## Utrustning

Dokument finns: Nej  
Fläns för omrörare: Nej  
Märkskylt: Nej  
Livsmedelsklassad: Ja  
Tankutlopp: inside Ø 100 mm  
Teknisk ritning finns: Nej  
Utloppstyp: DIN11851

## Översikt material

Material: Rostfritt 304  
Fixeringspunkt(er): RVS 304

## Dimensioner av tank

Cylinderhöjd: 4.550 mm  
Mått utlopp till marken: 700 mm  
Total höjd: 7.000 mm  
Ytterdiameter: 3.000 mm

## Omrörare

Kraft (kW): 9,50  
Position motor: at the top  
Typ av omrörare: anchor  
Varvtal: 35  
Spänning (Volt): three-phase

## Tjocklek på tank

Botten: 4 mm  
Cylinder: 3 mm  
Topp: 3 mm

**Mer**

Isolerad: Nej

Vikt: 2.000

---