

30000 liter tank i Rostfritt 304



224,000,00 kr /st exkl moms

Article type: second-hand mixing tank

Additional information: we can't give any guarantees about the agitator

Volumetric volume (L): 30.000 L

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no



Mobile tank: no

Top type: conical

Shape of tank: cylindrical

Bottom type: conical

Total discharge: yes

Fixation points: 3 non adjustable feet

Manway(s): RVS 304

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 2

Position of manway: at the top

Height manhole 1 (mm): 500 mm

Position 2nd manway: cylinder

Height manhole 2 (mm): 340 x 430 mm

Tank outlet: inside Ø 100 mm

Outlet type: DIN11851

Agitator: yes

Agitator type: anchor

Position engine: at the top

Number of revolutions: 35

Power: 9,50

Voltage: three-phase

Top: 3 mm

Cylinder: 3 mm

Bottom: 4 mm

Distance from outlet to ground: 700 mm

Outer diameter tank: 3.000 mm

Cylinder height: 4.550 mm

Total height of tank: 7.000 mm

Empty weight tank: 2.000

SKU: 565892

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Mobil tank: Nej

Övrig information: we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 30000



Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 100 mm
Teknisk ritning finns: Nej
Utloppstyp: DIN11851

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): RVS 304

Dimensioner av tank

Cylinderhöjd: 4.550 mm
Mått utlopp till marken: 700 mm
Total höjd: 7.000 mm
Ytterdiameter: 3.000 mm

Omrörare

Kraft (kW): 9,50
Position motor: at the top
Typ av omrörare: anchor
Varvtal: 35
Spänning (Volt): three-phase

Tjocklek på tank

Botten: 4 mm
Cylinder: 3 mm
Topp: 3 mm

Mer

Isolerad: Nej

Vikt: 2.000
