30000 liter tank i Rostfritt 304



237 000 SEK /st exkl moms

Article type: second-hand mixing tank
Additional information: we can't give any guarantees about the agitator
Volumetric volume (L): 30.000 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no

Top type: conical
Shape of tank: cylindrical
Bottom type: conical
Bottom outlet: yes
Total discharge: yes

Fixation points: 6 adjustable feet
Insulation material: rockwool
Outer jacket (ornamental wall): RVS 304L
Spray ball: RVS 304L
Manway(s): RVS 304L

Gasket manway(s): unknown
Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: no
Technical drawing included: no

Registration plate on the tank: no
Flange for agitator: no
Number of manways: 1
Position of manway: headside
Hinged lid: yes

Tank outlet: inside Ø 50 mm
Agitator: yes
Agitator type: propeller agitator
Position engine: at the top
Power: 1,50

Voltage: 380 V - three-phase
Internal diameter tank: 2.980 mm
Distance from outlet to ground: 1.900 mm
Outer diameter tank: 3.100 mm
Cylinder height: 4.300 mm

Total height of tank: 7.700 mm

SKU: 485855

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmospheric
Konfiguration: insulated
Mobil tank: Nej
Övrig information: we can’t give any guarantees about the agitator
Omrörare: Ja
Tankens form: cylindrical
Total urtappning: Yes
Typ av botten: conical
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304 (V2A)
Volym i liter: 30000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 50 mm
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): RVS 304
Isoleringsmaterial: Rockwool
Ytterbeklädnad: RVS 304L

Dimensioner av tank

Cylinderhöjd: 4.300 mm
Invändig diameter: 2.980 mm
Mått utlopp till marken: 1.900 mm
Total höjd: 7.700 mm
Ytterdiameter: 3.100 mm

Omrörare

Kraft (kW): 1,50
Position motor: at the top
Typ av omrörare: propeller agitator
Spänning (Volt): 380 V – three-phase

Tjocklek på ytterbeklädnad och isolering

Isoleringsmaterial: Rockwool

Mer

Isolerad: Ja