

30000 liter tank i Rostfritt 304



192,000,00 kr /st exkl moms

Additional information: Wool fat; Manhole diameter approx. 580 mm; metallic discoloration inside in the area of the upper bottom; some residues of previous content; manhole cover plated

Volumetric volume (L): 30.000 L

Pressure in tank: ATM - atmosferic

Max. temperature (°C): 70 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 90 L

Max Overpressure: 6 Bar

Max. working temperature: 160 °C

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: yes

Position of manway: cylinder

Outlet of tank: flange DN125

Cylinder: 6,20 mm

Bottom: 6,60 mm

Internal diameter tank: 2.480 mm

Cylinder height: 5.980 mm

Total height of tank: 8.050 mm

Empty weight tank: 2.300

SKU: 300318

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosfERIC

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 70 °C

Mobil tank: Nej

Övrig information: Wool fat; Manhole diameter approx. 580 mm; metallic discoloration inside in the area of the upper bottom; some residues of previous content; manhole cover plated

Omrörare: Nej

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 30000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Ja

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 5.980 mm

Invändig diameter: 2.480 mm

Total höjd: 8.050 mm

Tjocklek på tank

Botten: 6,60 mm

Cylinder: 6,20 mm

Mer

Isolerad: Nej

Vikt: 2.300