

30000 liter tank i Rostfritt 304



213,000,00 kr /st exkl moms

Additional information: Wool fat; Manhole diameter approx. 580 mm; metallic discoloration inside in the area of the upper bottom; Insulation jacket with dents and smaller sheet metal cutouts; some residues of previous content; manhole cover plated

Volumetric volume (L): 30.000 L

Pressure in tank: ATM - atmosferic
Max. temperature (°C): 70 °C
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes
Insulation: yes
Mobile tank: no

Total discharge: yes
Volume: 90 L
Max Overpressure: 6 Bar
Max. working temperature: 160 °C
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: yes
Position of manway: cylinder
Outlet of tank: flange DN125

Internal diameter tank: 2.480 mm
Outer diameter tank: 2.720 mm
Cylinder height: 5.980 mm
Total height of tank: 8.050 mm

SKU: 300428

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 70 °C

Mobil tank: Nej

Övrig information: Wool fat ; Manhole diameter approx. 580 mm; metallic discoloration inside in the area of the upper bottom; Insulation jacket with dents and smaller sheet metal cutouts; some residues of previous

Övrig information2: content;manhole cover plated; we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 30000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Ja

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 5.980 mm

Invändig diameter: 2.480 mm

Total höjd: 8.050 mm

Ytterdiameter: 2.720 mm

Mer

Isolerad: Ja
