

30000 liter tank i Rustfritt 304



289 000 SEK /st exkl moms

Article type: second-hand mixing tank

Additional information: 2 tanks with agitator, 1 tank without agitator; we can't give any guarantees about the agitator

Volumetric volume (L): 30.000 L



Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no

Top type: conical
Shape of tank: cylindrical
Bottom type: conical
Total discharge: yes
Fixation points: 6 adjustable feet

Outer jacket (ornamental wall): RVS 304
Manway(s): RVS 304
Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: no

Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Number of manways: 1
Position of manway: at the top

Agitator: yes
Agitator type: tripod
Position engine: at the top
Number of revolutions: 20
Power: 4,25

Voltage: three-phase
Internal diameter tank: 2.900 mm
Distance from outlet to ground: 500 mm
Outer diameter tank: 3.000 mm
Cylinder height: 4.650 mm

Feet height: 1.000 mm

Total height of tank: 6.700 mm

Empty weight tank: 2.600

SKU: 80126

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: insulated

Mobil tank: Nej

Övrig information: 2 tanks with agitator, 1 tank without agitator; we can't give any guarantees about the agitator

Omrörare: Ja

Tankens form: cylindrical

Total urtappning: Ja

Typ av botten: conical

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 30000



Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Livsmedelsklassad: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304
Fixeringspunkt(er): RVS 304
Ytterbeklädnad: RVS 304

Dimensioner av tank

Cylinderhöjd: 4.650 mm
Höjd på fötter: 1.000 mm
Invändig diameter: 2.900 mm
Mått utlopp till marken: 500 mm
Total höjd: 6.700 mm
Ytterdiameter: 3.000 mm

Omrörare

Kraft (kW): 4,25
Position motor: at the top
Typ av omrörare: tripad
Varvtal: 20
Spänning (Volt): three-phase

Mer

Isolerad: Ja
Vikt: 2.600