30000 liter tank i Syrafast 316



168 000 SEK /st exkl moms

Article type: second-hand storage tank
Additional information: the conical top has slight deformation
Volumetric volume (L): 30.000 L
Max. density P (kg/m³): 1.000
Ra inner weld: 0,80

Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Insulation: no
Mobile tank: no
Top type: conical
Shape of tank: cylindrical
Bottom type: conical

Total discharge: yes
Fixation points: 4 adjustable feet
Manway(s): RVS 316
Gasket manway(s): unknown
Fixation point(s): RVS 304

Suitable for food industry: yes
Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no

Number of manways: 1
Position of manway: cylinder
Height manhole 1 (mm): 320 mm x H 430 mm
Tank outlet: inside Ø 80 mm
Outlet type: DIN11851

Agitator: no, optional
Distance from outlet to ground: 350 mm
Outer diameter tank: 2.750 mm
Cylinder height: 5.050 mm
Total height of tank: 6.700 mm

Empty weight tank: 2.500

SKU: 481579

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmospheric
Konfiguration: single-skin
Maximal densitet för produkten: 1000
Mobil tank: Nej
Övrig information: the conical top has slight deformation
Omrörare: Nej
Ra innersvets: 0,80
Tankens form: cylindrical
Total urtappning: Yes
Typ av botten: conical
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 30000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 80 mm
Teknisk ritning finns: Nej
Utloppstyp: DIN11851

Översikt material

Material: Syrafast 316
Fixeringspunkt(er): RVS 304

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Dimensioner av tank

Cylinderhöjd: 5.050 mm
Mått utlopp till marken: 350 mm
Total höjd: 6.700 mm
Ytterdiameter: 2.750 mm

Mer

Isolerad: Nej
Vikt: 2.500

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se