

## 30395 liter tank i Rostfritt 304



### 369 000 SEK /st exkl moms

**Additional information:** Dairy; Double jacket with trickle ring - only suitable for unpressurized temperature control; dents in the double jacket; small cracks in the double jacket cladding; some of the connections have been wiped off; 2 dome screws on the feet are missing; pipe end cut flush

**Volumetric volume (L):** 30.395 L

**Pressure in tank:** vacuum

**Max. pressure (Bar):** 3,50 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 140 °C

**Material wet parts:** SS AISI 304 (V2A)

**Model:** vertical

**Configuration:** single-skin

**Heat exchanger:** no

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Type HE on the bottom:** heating/cooling jacket

**Type HE on the cylinder:** heating/cooling jacket

**Heat exchanger:** RVS 304

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** 80

**Number of revolutions:** 950

**Power:** 5,50

**Cylinder:** 6 mm

**Bottom:** 8 mm

**Internal diameter tank:** 2.800 mm

**Outer diameter tank:** 2.980 mm

**Cylinder height:** 4.000 mm

**Total height of tank:** 6.550 mm

**SKU:** 286847

---

Mer information

## Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 140 °C

Mobil tank: Nej

Övrig information: Dairy; Double jacket with trickle ring – only suitable for pressureless cooling; dents in the double jacket; small cracks in the double jacket lining; connections partially cut off; 2

Övrig information2: height-adjustable screws of the feet are missing ; pipe end cut flush

Omrörare: Nej

Övertryck: 3,50 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 30395

## Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

## Översikt material

Material: Rostfritt 304

## Dimensioner av tank

Cylinderhöjd: 4.000 mm

Invändig diameter: 2.800 mm

Total höjd: 6.550 mm

Ytterdiameter: 2.980 mm



## Omrörare

Kraft (kW): 5,50

Varvtal: 950

## Tjocklek på tank

Botten: 8 mm

Cylinder: 6 mm

## Mer

Värmeväxlare: RVS 304

Isolerad: Nej