

30395 liter tank i Rostfritt 304



376,000,00 kr /st exkl moms

Additional information: Dairy; Double jacket with trickle ring - only suitable for pressureless cooling; dents in the double jacket; small cracks in the double jacket lining; connections partially cut off; 2 height-adjustable screws of the feet are missing; pipe end cut flush

Volumetric volume (L): 30.395 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3,50 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 140 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Heat exchanger: RVS 304

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: 80

Number of revolutions: 950

Power: 5,50

Cylinder: 6 mm

Bottom: 8 mm

Internal diameter tank: 2.800 mm

Outer diameter tank: 2.980 mm

Cylinder height: 4.000 mm

Total height of tank: 6.550 mm

SKU: 286847

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 140 °C

Mobil tank: Nej

Övrig information: Dairy; Double jacket with trickle ring – only suitable for pressureless cooling; dents in the double jacket; small cracks in the double jacket lining; connections partially cut off; 2

Övrig information2: height-adjustable screws of the feet are missing ; pipe end cut flush

Omrörare: Nej

Övertryck: 3,50 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 30395

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 4.000 mm

Invändig diameter: 2.800 mm

Total höjd: 6.550 mm

Ytterdiameter: 2.980 mm



Omrörare

Kraft (kW): 5,50

Varvtal: 950

Tjocklek på tank

Botten: 8 mm

Cylinder: 6 mm

Mer

Värmeväxlare: RVS 304

Isolerad: Nej