

30395 liter tank i Syrafast 316



378 000 SEK /st exkl moms

Additional information: Double jacket with a drip ring—suitable only for pressureless tempering; spout cut off (see pictures)

Volumetric volume (L): 30.395 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3,50 Bar



Min. pressure (Bar): 1 Bar

Max. temperature (°C): 140 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: available

Internal diameter tank: 2.800 mm

Total height of tank: 6.400 mm

SKU: 709339

Mer information



Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: single-skin

Max. arbetstemperatur: 140 °C

Mobil tank: Nej

Övrig information: Double jacket with a drip ring—suitable only for pressureless tempering; spout cut off (see pictures)

Omrörare: Nej

Övertryck: 3,50 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Nej

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 30395

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Invändig diameter: 2.800 mm

Total höjd: 6.400 mm



Mer

Isolerad: Nej