

3100 liter tank i Rostfritt 304



75 000 SEK /st exkl moms

Additional information: Wall length inside: approx. 2150 mm; manhole diameter: approx. 460 mm; disk tap lever slightly bent; burlled plate (stainless steel 304) in the lower cylinder area; iso with stainless steel 304 jacket (partially welded, partially riveted); some slight detachment & minor dents in the iso jacket; external cooling element included with the following approx. dimensions: L= 1220 mm/ W= 1280 mm/ H= 1100 mm

Volumetric volume (L): 3.100 L
Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no
Total discharge: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no
Position of manway: headside

Outlet of tank: DN50 DIN 11851
Agitator: yes
Number of revolutions: 25
Power: 0,075
Outer diameter tank: 1.660 mm

Total height of tank: 1.900 mm
Total outer length: 2.700 mm

SKU: 300160

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: ATM – atmosfERIC

Konfiguration: insulated with heat-exchanger

Mobil tank: Nej

Övrig information: wall length inside: approx. 2150 mm; Manhole diameter: approx. 460 mm; butterfly valve; Knob plate (V2A) in the lower cylinder area; Iso with V2A jacket (partly welded, partly riveted); some slight

Övrig information2:

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 3100

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Total höjd: 1.900 mm

Ytterdiameter: 1.660 mm

Omrörare

Kraft (kW): 0,075

Varvtal: 25

Mer

Isolerad: Ja
