

3100 liter tank i Syrafast 316



133 000 SEK /st exkl moms

Additional information: 1 dent in the insulation jacket

Volumetric volume (L): 3.100 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 6 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 165 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: insulated

Heat exchanger: no

Insulation: yes

Mobile tank: no

Total discharge: yes

Max Overpressure: 6 Bar

Max onderdruk: 1 Bar

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: in the bottom

Outlet of tank: 54

Internal diameter tank: 1.380 mm

Outer diameter tank: 1.580 mm

Cylinder height: 1.580 mm

Total height of tank: 3.150 mm

SKU: 277078

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nyttillverkad/Begagnad: Begagnad
Arbetsstryck i tank: pressure and vacuum
Konfiguration: insulated
Max. arbetstemperatur: 165 °C
Mobil tank: Nej
Övrig information: 1 dent in the insulation jacket
Omrörare: Nej
Övertryck: 6 Bar
Total urtappning: Ja
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 3100

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 1.580 mm
Invändig diameter: 1.380 mm
Total höjd: 3.150 mm
Ytterdiameter: 1.580 mm

Mer

Isolerad: Ja
