

31000 liter tank i Rostfritt 304



454,000,00 kr /st exkl moms

Additional information: Heating jacket around approx. 2.380 mm of the lower cylinder height; Manhole approx. 430 x 540 mm; Tanks are currently hanging in a transport frame made of Fe; 1 loose ladder bracket is included in the scope of delivery (would have to be welded on site if desired)

Volumetric volume (L): 31.000 L

Pressure in tank: ATM - atmosferic
Max. temperature (°C): 80 °C
Material wet parts: SS AISI 304 (V2A)

Model: vertical
Configuration: insulated with heat-exchanger
Heat exchanger: yes
Insulation: yes
Mobile tank: no

Total discharge: yes
Max Overpressure: 3 Bar
Max. working temperature: 80 °C
Documents included: no
Technical drawing included: no

Registration plate on the tank: no
Flange for agitator: yes
Position of manway: cylinder
Outlet of tank: DN80 DIN 11851
Top: 4 mm

Cylinder: 3 mm
Bottom: 5 mm
Internal diameter tank: 2.800 mm
Outer diameter tank: 3.000 mm
Cylinder height: 4.750 mm

Total height of tank: 6.350 mm
Empty weight tank: 2.500

SKU: 433679

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Nyttillverkad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 80 °C

Mobil tank: Nej

Övrig information: Heating jacket around approx. 2.380 mm of the lower cylinder height;

Manhole approx. 430 x 540 mm; Tanks are currently hanging in a transport frame made of Fe; 1 loose ladder bracket is included in

Övrig information2: the scope of delivery (would have to be welded on site if desired); we can't give any guarantees about the heating/cooling jacket

Omrörare: Nej

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 31000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Ja

Märkskylt: Nej

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304



Dimensioner av tank

Cylinderhöjd: 4.750 mm
Invändig diameter: 2.800 mm
Total höjd: 6.350 mm
Ytterdiameter: 3.000 mm

Tjocklek på tank

Botten: 5 mm
Cylinder: 3 mm
Topp: 4 mm

Mer

Isolerad: Ja
Vikt: 2.500