

3120 liter tank i Rostfritt 304



99,000,00 kr /st exkl moms

Additional information: adhesive production; 1 reflux condenser is included in the scope of delivery (total height incl. reflux condenser); support brackets made of Fe; cut connections in the cylinder (see photos); some residues of previous content

Volumetric volume (L): 3.120 L

Pressure in tank: ATM - atmosferic
Material wet parts: SS AISI 304 (V2A)
Model: vertical

Configuration: single jacketed with heat-exchanger
Heat exchanger: yes
Insulation: no
Mobile tank: no
Total discharge: yes

Volume: 122 L
Type HE on the bottom: heating/cooling jacket
Type HE on the cylinder: heating/cooling jacket
Heat exchanger: RVS 304
Documents included: no

Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Position of manway: headside
Outlet of tank: flange DN80

Agitator: yes
Number of revolutions: 13 - 72
Power: 7,50
Top: 6 mm
Cylinder: 4 mm

Bottom: 4 mm
Internal diameter tank: 1.400 mm
Outer diameter tank: 1.460 mm
Cylinder height: 1.610 mm
Total height of tank: 5.400 mm

SKU: 267892

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: ATM – atmosferic

Konfiguration: single jacketed with heat-exchanger

Mobil tank: Nej

Övrig information: adhesive production; 1 reflux condenser is included in the scope of delivery (total height incl. reflux condenser); support brackets made of Fe; cut connections in the cylinder (see photos); some

Övrig information2: residues of previous content; we can't give any guarantees about the agitator

Omrörare: Ja

Total urtappning: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 3120

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Nej

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304



Dimensioner av tank

Cylinderhöjd: 1.610 mm
Invändig diameter: 1.400 mm
Total höjd: 5.400 mm
Ytterdiameter: 1.460 mm

Omrörare

Kraft (kW): 7,50
Varvtal: 13 – 72

Tjocklek på tank

Botten: 4 mm
Cylinder: 4 mm
Topp: 6 mm

Mer

Värmeväxlare: RVS 304
Isolerad: Nej