



3200 liter tank i Rostfritt 304



item available on order

Article type: brand new fermentation tank - type CCT-HIL

Additional information: *Included in the price: Kieselmann sample valve - vacuum valve - pressure gauge - safety valve - bunging valve, sprayball with pipe along side the outer jacket, 2 x butterfly valves on the outlets, steel transportation frame. 3 Bar - CE PED 97/23/EC TÜV - 10% Rx on the welding seams*

Capacity: 3.200 L

Maximal density of the product: 1.100

Ra inner weld: 0,80

Working pressure in tank: pressure

Overpressure: 3 Bar

Max. working temperature: 30 °C

Min. working temperature: -10 °C

Material wet parts: SS AISI 304L (V2A)

Model: vertical

Configuration: insulated with heat-exchanger

Heat exchanger: yes



Insulation: yes

Agitator: no

Mobile tank: no

Top type: dished

Shape of tank: cylindrical

Bottom type: strong conical 60 °

Total discharge: yes

Fixation points: 3 adjustable feet

Legs: Set of baseplates and adjusting pieces included

Type of HE on the cylinder: half pipe welded onto the outside of the innertank

Position HE: the middle part of the cilinder

Number of windings: 5

Height HE: 740 mm

Number of sections: 1

Water pressure HE: 3 Bar

Hydraulic test pressure: 4 Bar

Contact surface cylinder: 1,90 m²

Connection HE: 1 BSP

Type of HE on the bottom: dimple-jacket

Water pressure HE: 3 Bar

Hydraulic test pressure: 4 Bar

Total contact surface: 1,40

Connection HE: 1 BSP

Heat exchanger: RVS 304

Insulation material: PUR

Outer jacket (ornamental wall): RVS 304

Manway(s): RVS 304

Gasket manway(s): EPDM

Fixation point(s): RVS 304

Suitable for food industry: yes

Documents included: yes, optional

Technical drawing included: yes

Registration plate on the tank: yes

with inspection of: TUV

Flange for agitator: no

Number of manways: 1

Position manway: cylinder



Manway 2 (W): 440 x 340 mm

Spray ball: yes

Number: 1

Tank outlet: inside Ø 32 mm

Outlet type: DIN11851

Total outlet valve: yes

Type shut-off valve: butterfly valve

Adjustable legs: yes

Top: 4 mm

Cylinder: 3 mm

Bottom: 3 mm

Cylinder: 2

Insulation body: yes

Bottom: 2

Insulation bottom/sides: yes

finish of the outer jacket: welded

Internal diameter tank: 1.400 mm

Distance from outlet to ground: 250 mm

Outer diameter tank: 1.500 mm

Cylinder height: 1.500 mm

Total height of tank: 3.615 mm

Empty weight tank: 670

SKU: 6428

Additional Information

Volym i liter	3200
Nyttillverkad/Begagnad	Nyttillverkad
Livsmedelsklassad	Ja



Modell	Vertikal
Material	Rostfritt 304
Omrörare	Nej
Uppvärmning/kylning	Ja
Isolerad	Ja
Trycktank	Ja
Mått utlopp till marken	250 mm
Ytterdiameter	1.500 mm
Cylinderhöjd	1.500 mm
Total höjd	3.615 mm
Vikt	670