

## 3200 liter tank i Syrafast 316



**240,000,00 SEK /st exkl moms**

**Additional information:** Food  
**Volumetric volume (L):** 3.200 L  
**Pressure in tank:** pressure and vacuum  
**Max. pressure (Bar):** 3 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 150 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** insulated with heat-exchanger

**Heat exchanger:** yes

**Insulation:** yes

**Mobile tank:** no

**Total discharge:** yes

**Max Overpressure:** 3 Bar

**Max onderdruk:** 1 Bar

**Max. working temperature:** 150 °C

**Type HE on the cylinder:** heating/cooling jacket

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Position of manway:** headside

**Outlet of tank:** available

**Agitator:** yes

**Power:** 1,50

**Cylinder:** 6 mm

**Bottom:** 7 mm

**Internal diameter tank:** 1.500 mm

**Outer diameter tank:** 1.700 mm

**Cylinder height:** 1.600 mm

**Total height of tank:** 3.150 mm

**SKU:** 570545

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: insulated with heat-exchanger

Max. arbetstemperatur: 150 °C

Mobil tank: Nej

Övrig information: Food; we can't give any guarantees about the heating/cooling jacket; we can't give any guarantees about the agitator

Omrörare: Ja

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 3200

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316



## **Dimensioner av tank**

Cylinderhöjd: 1.600 mm  
Invändig diameter: 1.500 mm  
Total höjd: 3.150 mm  
Ytterdiameter: 1.700 mm

## **Omrörare**

Kraft (kW): 1,50

## **Tjocklek på tank**

Botten: 7 mm  
Cylinder: 6 mm

## **Mer**

Isolerad: Ja