32000 liter tank i GAP/Plast



142 000 SEK /st exkl moms

item available on order

Article type: brand new storage tank - type MP-SEF
Additional information: lid for manway in stainless-steel (SS); set of anchorage points in stainless-steel (SS) included; tank will be delivered with Food grade certificate.

Volumetric volume (L): 32.000 L
Max. density P (kg/m³): 1.300
Pressure in tank: ATM - atmosferic

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Max. temperature (°C): 60 °C
Min. temperature (°C): -10 °C
Material wet parts: polyester (fiberglass)
Model: vertical
Configuration: single-skin

Heat exchanger: no
Insulation: no
Mobile tank: no
Top type: dished
Shape of tank: cylindrical

Bottom type: flat
Total discharge: no
Fixation points: attachment points
Outer jacket (ornamental wall): polyester
Manway(s): RVS 316

Valve: RVS 316L
Fixation point(s): RVS 304
Suitable for food industry: yes
Documents included: yes, optional
Technical drawing included: yes

Registration plate on the tank: yes
Flange for agitator: no
Number of manways: 1
Position of manway: cylinder
Height manhole 1 (mm): 320 mm x H 435 mm

Tank outlet: inside Ø 50 mm
Outlet type: Guillement 2"
Total outlet valve: yes
Agitator: no
Internal diameter tank: 3.000 mm

Outer diameter tank: 3.050 mm
Total height of tank: 5.082 mm
Empty weight tank: 828

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

SKU: 374642

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: GAP/Plast
Modell: Vertikal
Nytillverkad/Begagnad: Nytillverkad
Arbetstryck i tank: ATM – atmospheric
Konfiguration: single-skin
Max. arbetstemperatur: 60 °C
Maximal densitet för produkten: 1300
Min. arbetstemperatur: -10 °C
Mobil tank: Nej
Övrig information: lid for manway in stainless-steel (SS); set of anchorage points in stainless-steel (SS) included; tank will be delivered with Food grade certificate.
Omrörare: Nej
Tankens form: cylindrical
Total urtappning: Nej
Typ av botten: flat
Uppvärmning/kylning: Nej
Vätskeberörd yta: polyester (fiberglass)
Volym i liter: 32000

Utrustning

Fläns för omrörare: Nej
Märkskylt: Ja
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 50 mm
Teknisk ritning finns: Ja
Utloppstyp: Guillement 2"
Utloppsventil: Ja

Översikt material

Material: GAP/Plast
Fixeringspunkt(er): RVS 304
Ytterbeklädnad: polyester

Dimensioner av tank

Invändig diameter: 3.000 mm
Total höjd: 5.082 mm
Ytterdiameter: 3.050 mm

Mer

Isolerad: Nej
Vikt: 828