

## 32000 liter tank i GAP/Plast



**142,000,00 kr /st exkl moms**

item available on order

**Article type:** brand new storage tank - type MP-SEF

**Additional information:** lid for manway in stainless-steel (SS); set of anchorage points in stainless-steel (SS) included; tank will be delivered with Food grade certificate.

**Volumetric volume (L):** 32.000 L

**Max. density P (kg/m<sup>3</sup>):** 1.300

**Pressure in tank:** ATM - atmosferic



**Max. temperature (°C):** 60 °C  
**Min. temperature (°C):** -10 °C  
**Material wet parts:** polyester (fiberglass)  
**Model:** vertical  
**Configuration:** single-skin

**Heat exchanger:** no  
**Insulation:** no  
**Mobile tank:** no  
**Top type:** dished  
**Shape of tank:** cylindrical

**Bottom type:** flat  
**Total discharge:** no  
**Fixation points:** attachment points  
**Outer jacket (ornamental wall):** polyester  
**Manway(s):** RVS 316

**Valve:** RVS 316L  
**Fixation point(s):** RVS 304  
**Suitable for food industry:** yes  
**Documents included:** yes, optional  
**Technical drawing included:** yes

**Registration plate on the tank:** yes  
**Flange for agitator:** no  
**Number of manways:** 1  
**Position of manway:** cylinder  
**Height manhole 1 (mm):** 320 mm x H 435 mm

**Tank outlet:** inside Ø 50 mm  
**Outlet type:** Guillement 2"  
**Total outlet valve:** yes  
**Agitator:** no  
**Internal diameter tank:** 3.000 mm

**Outer diameter tank:** 3.050 mm  
**Total height of tank:** 5.082 mm  
**Empty weight tank:** 828

SKU: 5648

## Mer information

### Beskrivning av produkt

Livsmedelsklassad: Ja

Material: GAP/Plast

Modell: Vertikal

Nyttillverkad/Begagnad: Nyttillverkad

Arbetstryck i tank: ATM – atmosferic

Konfiguration: single-skin

Max. arbetstemperatur: 60 °C

Maximal densitet för produkten: 1300

Min. arbetstemperatur: -10 °C

Mobil tank: Nej

Övrig information: lid for manway in stainless-steel (SS); set of anchorage points in stainless-steel (SS) included; tank will be delivered with Food grade certificate.

Omrörare: Nej

Tankens form: cylindrical

Total urtappning: Nej

Typ av botten: flat

Uppvärmning/kylning: Nej

Vätskeberörd yta: polyester (fiberglass)

Volym i liter: 32000



## Utrustning

Fläns för omrörare: Nej  
Märkskylt: Ja  
Livsmedelsklassad: Ja  
Tankutlopp: inside Ø 50 mm  
Teknisk ritning finns: Ja  
Utloppstyp: Guillement 2"  
Utloppsventil: Ja

## Översikt material

Material: GAP/Plast  
Fixeringspunkt(er): RVS 304  
Ytterbeklädnad: polyester

## Dimensioner av tank

Invändig diameter: 3.000 mm  
Total höjd: 5.082 mm  
Ytterdiameter: 3.050 mm

## Mer

Isolerad: Nej  
Vikt: 828