32000 liter tank i Rostfritt 304



316 000 SEK /st exkl moms

Article type: second-hand storage tank
Additional information: The tank has never been used.
Volumetric volume (L): 32.000 L
Max. density P (kg/m³): 1.200
Ra inner weld: 0,80

Finish stainless steel: 2B
Pressure in tank: ATM - atmosferic
Max. temperature (°C): 60 °C
Min. temperature (°C): -10 °C
Material wet parts: SS AISI 304L (V2A)

Model: vertical
Configuration: single-skin
Heat exchanger: no
Insulation: no
Mobile tank: no

Top type: conical 13 °
Shape of tank: cylindrical
Bottom type: conical 20 °
Total discharge: yes
Fixation points: 4 non adjustable feet

Manway(s): RVS 304L
Gasket manway(s): EPDM
Fixation point(s): RVS 304L
Suitable for food industry: yes
Documents included: yes, optional

Technical drawing included: yes
Registration plate on the tank: yes
Flange for agitator: no
Number of manways: 1
Position of manway: at the top

Height manhole 1 (mm): 500 mm
Hinged lid: yes
Tank outlet: inside Ø 80 mm
Outlet type: DIN11851 male
Total outlet valve: no, optional

Top: 2 mm
Cylinder: 2 mm
Bottom: 4 mm
Distance from outlet to ground: 395 mm
Outer diameter tank: 2.984 mm

Cylinder height: 4.500 mm
Total height of tank: 5.872 mm
Empty weight tank: 1.250

SKU: 480507

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Rostfritt 304
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmospheric
Finish rostfritt stål: 2b
Konfiguration: single-skin
Max. arbetstemperatur: 60 °C
Maximal densitet för produkten: 1200
Min. arbetstemperatur: -10 °C
Mobil tank: Nej
Övrig information: The tank has never been used.
Omrörare: Nej
Ra innersvets: 0,80
Tankens form: cylindrical
Total urtappning: Yes
Typ av botten: conical 20 °
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 304L (V2A)
Volym i liter: 32000

Utrustning
Fläns för omrörare: Nej
Märkskylt: Ja
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 80 mm
Teknisk ritning finns: Ja
Utloppstyp: DIN11851 male

Översikt material
Material: Rostfritt 304
Fixeringspunkt(er): RVS 304L

Dimensioner av tank
Cylinderhöjd: 4.500 mm
Mått utlopp till marken: 395 mm
Total höjd: 5.872 mm
Ytterdiameter: 2.984 mm

Tjocklek på tank
Botten: 4 mm
Cylinder: 2 mm
Topp: 2 mm

Mer
Isolerad: Nej
Vikt: 1.250