

32000 liter tank i Syrafast 316



423 000 SEK /st exkl moms

Additional information: Chemistry; Diameter of manhole cylinder 500 mm (manhole cover screws mostly missing); one vessel has 1 foot, the other vessel has 2 feet pressed into the lower bottom (this vessel also has 1 connection pressed into the upper bottom and the heating coil is pressed in at one point); the pressed-in feet would have to be repaired on site before the tanks are reinstalled; external insulating rings

made of Fe (partially slightly damaged); 1 vessel in the outlet with flanged reduction (inner pipe diameter approx. 55 mm); see photos; some residues of previous content; manhole cover plated

Volumetric volume (L): 32.000 L

Pressure in tank: vacuum

Max. pressure (Bar): 3 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C

Material wet parts: SS AISI 316 (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 80 L

Max Overpressure: 6 Bar

Type HE on the bottom: half pipe welded onto the outside of the innertank

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Outlet of tank: 100

Cylinder: 8 mm

Bottom: 10 mm

Internal diameter tank: 2.400 mm

Cylinder height: 6.970 mm

Total height of tank: 9.050 mm

Empty weight tank: 7.000

SKU: 309052

Mer information

Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Chemistry; Manhole cylinder diameter 500 mm (most of the manhole cover screws are missing); 1 tank has 1 foot pressed into the lower bottom and the other tank has 2 feet pressed into the lower

Omrörare: Nej

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 32000

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 6.970 mm
Invändig diameter: 2.400 mm
Total höjd: 9.050 mm

Tjocklek på tank

Botten: 10 mm
Cylinder: 8 mm

Mer

Isolerad: Nej
Vikt: 7.000