32000 liter tank i Syrafast 316



425 000 SEK /st exkl moms

Additional information: Diameter of manhole cylinder 500 mm (manhole cover screws mostly missing); one vessel has 1 foot, the other vessel has 2 feet pressed into the lower bottom (this vessel also has 1 connection pressed into the upper bottom and the heating coil is pressed in at one point); the pressed-in feet would have to be repaired on site before the tanks are reinstalled; external insulating rings made of Fe (partially slightly damaged); 1 vessel in the outlet with flanged reduction (inner pipe diameter approx. 55

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

mm); see photos; some residues of previous content; manhole cover plated
Volumetric volume (L): 32.000 L
Pressure in tank: pressure and vacuum
Max. pressure (Bar): 3 Bar
Min. pressure (Bar): 1 Bar

Max. temperature (°C): 200 °C
Material wet parts: SS AISI 316 (V4A)
Model: vertical
Configuration: single-skin
Heat exchanger: no

Insulation: no
Mobile tank: no
Total discharge: yes
Volume: 80 L
Max Overpressure: 6 Bar

Type HE on the bottom: half pipe welded onto the outside of the innertank
Documents included: no
Technical drawing included: no
Registration plate on the tank: yes
Flange for agitator: no

Outlet of tank: 100
Cylinder: 8 mm
Bottom: 10 mm
Internal diameter tank: 2.400 mm
Cylinder height: 6.970 mm

Total height of tank: 9.050 mm
Empty weight tank: 7.000

SKU: 429674

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: pressure and vacuum
Konfiguration: single jacketed with heat-exchanger
Max. arbetstemperatur: 200 °C
Mobil tank: Nej
Övrig information: Chemistry; Manhole cylinder diameter 500 mm (most of the manhole cover screws are missing); 1 tank has 1 foot pressed into the lower bottom and the other tank has 2 feet pressed into the lower
Övrig information2:
Omrörare: Nej
Övertryck: 3 Bar
Total urtappning: Yes
Undertryck (vakuum): 1 Bar
Trycktank: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 32000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Ja
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank
Cylinderhöjd: 6.970 mm
Invändig diameter: 2.400 mm
Total höjd: 9.050 mm

Tjocklek på tank
Botten: 10 mm
Cylinder: 8 mm

Mer
Isolerad: Nej
Vikt: 7.000

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se