

## 32000 liter tank i Syrafast 316



**432,000,00 kr /st exkl moms**

**Additional information:** Chemistry; Manhole cylinder diameter 500 mm (most of the manhole cover screws are missing); 1 tank has 1 foot pressed into the lower bottom and the other tank has 2 feet pressed into the lower bottom; (this tank also has 1 connection pressed into the upper bottom and the heating coil is pressed in at one point; the damaged feet would have to be repaired on site before the tanks were reinstalled;

external insulating rings made of Fe (some slightly damaged); 1 tank in the outlet with flanged reduction (inner pipe diameter approx. 55 mm); see photos; some residues of previous content; manhole cover plated

**Volumetric volume (L):** 32.000 L

**Pressure in tank:** pressure and vacuum

**Max. pressure (Bar):** 3 Bar

**Min. pressure (Bar):** 1 Bar

**Max. temperature (°C):** 200 °C

**Material wet parts:** SS AISI 316 (V4A)

**Model:** vertical

**Configuration:** single jacketed with heat-exchanger

**Heat exchanger:** yes

**Insulation:** no

**Mobile tank:** no

**Total discharge:** yes

**Volume:** 80 L

**Max Overpressure:** 6 Bar

**Type HE on the bottom:** half pipe welded onto the outside of the innertank

**Documents included:** no

**Technical drawing included:** no

**Registration plate on the tank:** yes

**Flange for agitator:** no

**Outlet of tank:** 100

**Cylinder:** 8 mm

**Bottom:** 10 mm

**Internal diameter tank:** 2.400 mm

**Cylinder height:** 6.970 mm

**Total height of tank:** 9.050 mm

**Empty weight tank:** 7.000

**SKU:** 309052

## Mer information

### Beskrivning av produkt

Material: Syrafast 316

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetsstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 200 °C

Mobil tank: Nej

Övrig information: Chemistry; Manhole cylinder diameter 500 mm (most of the manhole cover screws are missing); 1 tank has 1 foot pressed into the lower bottom and the other tank has 2 feet pressed into the lower

Övrig information2:

Omrörare: Nej

Övertryck: 3 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 316 (V4A)

Volym i liter: 32000

### Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

### Översikt material

Material: Syrafast 316



## Dimensioner av tank

Cylinderhöjd: 6.970 mm  
Invändig diameter: 2.400 mm  
Total höjd: 9.050 mm

## Tjocklek på tank

Botten: 10 mm  
Cylinder: 8 mm

## Mer

Isolerad: Nej  
Vikt: 7.000