32000 liter tank i Syrafast 316



168 000 SEK /st exkl moms

Additional information: Electric heating cable around parts of the vessel; diameter manhole cylinder 600 mm; insulation with larger cut-outs in insulation and insulating jacket; vessel is currently fitted with a transport lock; 1 pipe inside the vessel (see photos); manhole cover plated
Volumetric volume (L): 32.000 L
Pressure in tank: ATM - atmosferic

PROCESSÖVERSKOTT AB

Rodervägen 57
891 78 Bonässund
info@processoverskott.se

Material wet parts: SS AISI 316 (V4A)
Model: vertical

Configuration: insulated
Heat exchanger: no
Insulation: yes
Mobile tank: no
Total discharge: yes

Documents included: no
Technical drawing included: no
Registration plate on the tank: no
Flange for agitator: no
Outlet of tank: available

Top: 6 mm
Cylinder: 6 mm
Internal diameter tank: 2.300 mm
Outer diameter tank: 2.480 mm
Cylinder height: 7.250 mm

Total height of tank: 9.150 mm

SKU: 427385

Mer information

Beskrivning av produkt

Material: Syrafast 316
Modell: Vertikal
Nytillverkad/Begagnad: Begagnad
Arbetstryck i tank: ATM – atmosferic
Konfiguration: insulated with heat-exchanger
Mobil tank: Nej
Övrig information: Chemistry; Electric heating cables around parts of the tank; Diameter manhole cylinder 600 mm; Insulation with larger cutouts in insulation and insulation jacket; tank is currently provided with a
Övrig information2: transport lock; 1 pipe inside the tank (see photos); manhole cover plated; we can't give any guarantees about the heating/cooling jacket
Omrörare: Nej
Total urtappning: Ja
Uppvärmning/kylning: Ja
Vätskeberörd yta: SS AISI 316 (V4A)
Volym i liter: 32000

Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Teknisk ritning finns: Nej

Översikt material

Material: Syrafast 316

Dimensioner av tank

Cylinderhöjd: 7.250 mm
Invändig diameter: 2.300 mm
Total höjd: 9.150 mm
Ytterdiameter: 2.480 mm

Tjocklek på tank
Cylinder: 6 mm
Topp: 6 mm

Mer
Isolerad: Ja