

32300 liter tank i Rostfritt 304



422,000 SEK /st exkl moms

Additional information: Sterile tank in a dairy; Double jacket with trickle ring - only suitable for unpressurized tempering; dents in the double jacket in the area of the support timbers; maximum temperature for sterilization in the inner tank 145° C; specified total height according to drawing; 1 former connection in the upper bottom was welded shut by the previous operator (see photos)

Volumetric volume (L): 32.300 L

Pressure in tank: pressure and vacuum

Max. pressure (Bar): 3,50 Bar

Min. pressure (Bar): 1 Bar

Max. temperature (°C): 50 °C

Material wet parts: SS AISI 304 (V2A)

Model: vertical

Configuration: single jacketed with heat-exchanger

Heat exchanger: yes

Insulation: no

Mobile tank: no

Total discharge: yes

Volume: 4.700 L

Max. working temperature: 50 °C

Type HE on the bottom: heating/cooling jacket

Type HE on the cylinder: heating/cooling jacket

Documents included: no

Technical drawing included: no

Registration plate on the tank: yes

Flange for agitator: no

Position of manway: headside

Outlet of tank: available

Top: 9,50 mm

Cylinder: 7,50 mm

Bottom: 7,50 mm

Internal diameter tank: 2.785 mm

Outer diameter tank: 3.000 mm

Cylinder height: 4.500 mm

Total height of tank: 8.100 mm

SKU: 490353

Mer information

Beskrivning av produkt

Material: Rostfritt 304

Modell: Vertikal

Nyttillverkad/Begagnad: Begagnad

Arbetstryck i tank: pressure and vacuum

Konfiguration: single jacketed with heat-exchanger

Max. arbetstemperatur: 50 °C

Mobil tank: Nej

Övrig information: Sterile tank in a dairy; Double jacket with trickle ring – only suitable for unpressurized tempering; dents in the double jacket in the area of the support timbers; maximum temperature for

Övrig information2: sterilization in the inner tank 145° C; specified total height according to drawing; 1 former connection in the upper bottom was welded shut by the previous operator (see photos)

Omrörare: Nej

Övertryck: 3,50 Bar

Total urtappning: Ja

Undertryck (vakuum): 1 Bar

Trycktank: Ja

Uppvärmning/kylning: Ja

Vätskeberörd yta: SS AISI 304 (V2A)

Volym i liter: 32300

Utrustning

Dokument finns: Nej

Fläns för omrörare: Nej

Märkskylt: Ja

Teknisk ritning finns: Nej

Översikt material

Material: Rostfritt 304

Dimensioner av tank

Cylinderhöjd: 4.500 mm
Invändig diameter: 2.785 mm
Total höjd: 8.100 mm
Ytterdiameter: 3.000 mm

Tjocklek på tank

Botten: 7,50 mm
Cylinder: 7,50 mm
Topp: 9,50 mm

Mer

Isolerad: Nej