

32700 liter tank i Syrafast 316



344,000,00 kr /st exkl moms

Article type: second-hand storage tank

Additional information: The tank has never been used.

Volumetric volume (L): 32.700 L

Max. density P (kg/m³): 1.200

Pressure in tank: ATM - atmosferic

Material wet parts: SS AISI 316L (V4A)

Model: vertical

Configuration: single-skin

Heat exchanger: no



Insulation: no

Mobile tank: no

Top type: conical 15 °

Shape of tank: cylindrical

Bottom type: conical 20 °

Bottom outlet: yes

Total discharge: yes

Fixation points: 4 non adjustable feet

Manway(s): RVS 316

Gasket manway(s): EPDM

Fixation point(s): RVS 304L

Suitable for food industry: yes

Documents included: no

Technical drawing included: no

Registration plate on the tank: no

Flange for agitator: no

Number of manways: 2

Position of manway: cylinder

Height manhole 1 (mm): 440 mm x H 308 mm

Hinged lid: yes

Position 2nd manway: headside

Height manhole 2 (mm): 500

CIP spray ball: no

Tank outlet: inside Ø 80 mm

Outlet type: DIN 11851

Total outlet valve: no, optional

Top: 2 mm

Cylinder: 2 mm

Bottom: 3 mm

Distance from outlet to ground: 405 mm

Outer diameter tank: 2.984 mm

Cylinder height: 4.500 mm

Height of top: 382 mm

Height of bottom: 595 mm
Feet height: 1.000 mm
Total height of tank: 5.882 mm

Empty weight tank: 2.900

SKU: 480552

Mer information

Beskrivning av produkt

Livsmedelsklassad: Ja
Material: Syrafast 316
Modell: Vertikal
Nyttillverkad/Begagnad: Begagnad
Arbetsstryck i tank: ATM – atmosferic
Konfiguration: single-skin
Maximal densitet för produkten: 1200
Mobil tank: Nej
Övrig information: The tank has never been used.
Omrörare: Nej
Tankens form: cylindrical
Total urtappning: Ja
Typ av botten: conical 20 °
Uppvärmning/kylning: Nej
Vätskeberörd yta: SS AISI 316L (V4A)
Volym i liter: 32700



Utrustning

Dokument finns: Nej
Fläns för omrörare: Nej
Märkskylt: Nej
Livsmedelsklassad: Ja
Tankutlopp: inside Ø 80 mm
Teknisk ritning finns: Nej
Utloppstyp: DIN 11851

Översikt material

Material: Syrafast 316
Fixeringspunkt(er): RVS 304L

Dimensioner av tank

Cylinderhöjd: 4.500 mm
Höjd på fötter: 1.000 mm
Mått utlopp till marken: 405 mm
Total höjd: 5.882 mm
Ytterdiameter: 2.984 mm

Tjocklek på tank

Botten: 3 mm
Cylinder: 2 mm
Topp: 2 mm

Mer

Isolerad: Nej
Vikt: 2.900